

# Maxon Shut-Off and Vent Valves General Purpose



*2.5" Series 808  
position "TO"*



*2" Series 5000-CP  
position "L"  
with stainless steel body*



*2.5" Series STO-ACP  
position "R"*

- **Electrically actuated valves shut off gas or oil lines** reliably.
- **Normally open versions available** for vent or process purge lines with Maxon's long-lasting metal-to-metal seating.
- **Application flexibility provided** with 3/8" through 6" diameter line sizes,  $C_v$  flow factors up to 1230, and line pressures up to 600 PSIG.
- **All Maxon top assembly enclosures meet approval sanctions:**
  - NEMA 1, 3, 3S, 4, and 12; CSA 2, 4, and 5; Available with NEMA 4X trim (optional)

## Normally open or normally closed valves



*4" Series 5000-SCP  
position "L"*



*1.5" Series STO-M  
position "L"*



*4" Series 7000  
position "L"*

- **Sanctioned service valve approvals:**

- FM (Factory Mutual) sanctioned
- UL (Underwriters Laboratories) sanctioned
- CGA (Canadian Gas Association) sanctioned
- IRI (Industrial Risk Insurers) approvable for block/bleed/vent systems
- Contact your Maxon sales representative for international sanctions information

- **Handles flowing fluid temperatures:**

- Rising stem bodies from -20°F (-28°C) to +140°F (+60°C)
- Swinging gate bodies from -20°F (-28°C) to +550°F (+288°C)
- Any ambient temperature from -20°F (-28°C) to +140°F (+60°C)

- **Valve body connections designed to ANSI** (American National Standards Institute) standards. ISO (International Standards Organization) standards also available.

- **Various application requirements met** with manual reset or automatic reset motorized operators.

- **Minimize line pressure drops** with straight-through flow swinging gate or rising stem (guillotine action) valve bodies



## Maxon Valves – large or small, gas or oil, open or closed



*1" Series 23300  
position "L"*



*1" Series 8730  
position "TO"*



*1" Series 760  
position "L"*

- **Minimal field maintenance required.**
  - **Positive visual indication of valve body position** is provided by large two-color open-shut indicator.
  - **Bodies built for heavy duty industrial service** of one-piece cast iron, cast steel or cast stainless steel.
  - **Installation piping convenience obtained** from field rotatable top assemblies.
  - **Special operating features** available in Special Service Packaged versions.
  - **Micro-lapped seating** wears in, not out.
-

## Accessory Options



*1.25" Series 808  
position "R",  
with wheel & chain assembly*



*1" Series 25300  
position "L"  
with socket welded nipples & flanges*

- **Positive indication of valve body position provided through:**
  - Auxiliary SPDT and DPDT signal switches mounted inside valve top enclosure.
  - Proof-of-open and/or Proof-of-closed position switches.
- **Built-in over travel valve body design** meets requirements of insurance standards.
- **External junction box requirement eliminated** with built-in valve wiring compartment and electrical terminal block.
- **Manual reset valves may be mounted in overhead lines** with use of wheel and chain option.
- **Companion flange sets available** to simplify installation.

